

VIBRATING COMPACTION HAMMER

Standard: EN 13286-4 (Annex A), BS 1377:4, BS 1924:2, EN 12697-32

Vibration Compaction Hammer

The hammer is used for compacting of Proctor and CBR Soil specimen. By changing appropriate tamping foot, it also can be used for compacting concrete cube or beam specimens and compacting asphalt in the percentage refusal density test (PRD Test). **Supplied without accessories** which have to be order separately.



Technical Specifications :

Model Number	NL 5021 X / 001
Alternate Code	DH 0810
Impact Rate	2900 / 3480 VPM
Product Dimension	440 (L) x 95 (W) x 240 (H) (mm)
Approx. Weight	6.3 kg
Power	220~240 V, 1050 W, 1 Ph, 50 / 60 Hz, 4.5 A

Optional Accessories :

Model Number	Accessories Description	Weight
NL 5021 X / 001 – A 001N	Supporting Frame	63 kg
NL 5021 X / 001 – A 002	Proctor Tamping Foot (Ø 100 mm) c/w Steel Shank	1.8 kg
NL 5021 X / 001 – A 003	Proctor, CBR & PRD Tamping Foot Ø 145 mm c/w Steel Shank	3.1 kg
NL 5021 X / 001 – A 004	100 mm Concrete Cube Tamping Foot 90 x 90 mm c/w Steel Shank	2.3 kg
NL 5021 X / 001 – A 005	150 mm Concrete Cube Tamping Foot 140 x 140 mm c/w Steel Shank	4.1 kg



NL 5021 X / 001 – A004
& A005



NL 5021 X / 001 – A002,
A003 & A006